

**VIS**

LUBRICANT FOR ROTARY COMPRESSORS

**DESCRIPTION**

**VIS** are premium ash-free lubricants for the lubrication of rotary air compressors operate in high temperature (discharge temperature of up to 90 °C) with oil maintenance up to 4,000 hrs in well-maintained machines operating under standard conditions according to the equipment manufacturer.

**ADVANTAGES**

- High oxidation and good thermal stability
- Excellent hydrolytic stability
- Prevents sludge formation, good protection against corrosion
- Very low acid number
- Good demulsifying and foam behavior

**TECHNICAL INFORMATION**

TYPICAL CHARACTERISTICS	METHOD	VIS 32	VIS 46
Specific Gravity (Kg/L at 20 °C)	ASTM D4052	0.848	0.853
Viscosity at 40 °C	ASTM D445	33	46
Viscosity at 100 °C	ASTM D445	5.7	7.2
Viscosity Index	ASTM D2270	118	118
Flash point COC (°C)	ASTM D92	226	230
Pour point (°C)	ASTM D97	-39	-39

**PERFORMANCE**

**VIS** meets the following standards:

- DIN 51506 – VBL, VCL, VDL
- ISO / DP 6521 (DAA, DAB, DAH, DAG)

## SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and in-use monitoring of your lubricants. Please contact your technical sales representative.

## IMPORTANT NOTICE

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary. The safety data sheet of this product is available at [www.motul.com](http://www.motul.com)

**VILUBE** member of **MOTUL Asia Pacific**

Pearl Plaza Building, 29th Floor, 561A Dien Bien Phu / Ward 25, Binh Thanh Dist. / MCMC, Vietnam

Tel +84 28 3513 6015, Fax+84 28 3513 6027